

## ATF Additives

### DESCRIPTION

Due to the additives contained, rubber and plastic seals in transmissions receive optimal care. Leaks in the transmission caused by hardened or brittle seals are prevented or remedied. In addition, holes and ducts in the transmission are cleaned, the performance of the oil is revitalized and the shifting operations are improved. Using ATF Additives, the service life of automatic transmissions can be lengthened and repair costs reduced.

### PROPERTIES

- Prevents oil loss
- Regenerates seals
- Cleans and protects
- Damps down shifting operations and protects from wear
- Prevents deterioration of oil and oxidation
- Lowers repair costs and lengthens the service life

### TECHNICAL DATA

Color	:	brown	
Viscosity at +40 °C	:	approx. 166 mm <sup>2</sup> /s	DIN 51562
Viscosity at +100 °C	:	approx. 26 mm <sup>2</sup> /s	DIN 51562
Density at 15 °C	:	approx. 0.888 kg/dm <sup>3</sup>	DIN 51757
Refractive index 20 °C	:	approx. 1.478	

### AREAS OF APPLICATION

Suitable for all automatic transmissions that are filled with ATF II and ATF III oils.

### APPLICATION

Mix ATF Additive into the gear oil using the dipstick. 250 ml are sufficient for up to 8 liters of oil.

### AVAILABLE PACK SIZES

ATF Additives                      250 ml    Part no.                      5135                      D-GB-I-P-E

PI 00/07/07

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

