

Bio-Sägekettenöl (Bio Saw-Chain Oil)

DESCRIPTION

Bio Saw-Chain Oil is a high-performance oil based on high-quality vegetable oils. This special formulation of bio saw-chain oils guarantees rapid biodegradation and toxicological safety. Outstanding adhesive properties and optimum lubricating property ensure that all moving parts such as chain links and joints have the optimum lubrication and are protected from wear. The product's favourable viscosity and temperature behaviour guarantees year-round use at both high and low outside temperatures. Bio Saw-Chain Oil has been awarded the highest commendation by KWF (Committee for Forests and Forestry [Germany]).

TECHNICAL DATA

ASTM colour	:	1.5	
Density at 15 °C	:	0.92	g/cm ³
Flash point	:	> 250	°C
Pour point	:	-25	°C
ISO VG class	:	100	
Loading capacity according to Brugger	:	30	N/mm ²
Biodegradability after 21 days	:	> 98	%
Water endangerment category (Germany)	:	0	
Stability (shelf life)	:	24	months (from date of filling)

APPLICATION

All high-performance motor-saw chains under extreme conditions such as sawing hardwoods.

INSTRUCTIONS

Abide by the instructions of the motor-saw and chain manufacturers.

AVAILABLE PACK SIZE

Bio Saw-Chain Oil	1 l	Part no. 1280
	5 l	Part no. 1281

PI 01/02/01

Our information is based on thorough research and may be considered reliable, although not legally binding.

