

Hypoid-Getriebeöl (Gear Oil) SAE 85W-90

DESCRIPTION

Hypoid Gear Oil SAE 85W-90 is a high-performance, high-pressure gear oil manufactured from carefully selected base oils and multifunctional "extreme pressure" additives. It is suitable for powered transmission and axle drives, especially for high-load hypoid transmissions.

PROPERTIES

- highest pressure-absorption capability
- reduces wear
- reduces running noise
- excellent viscosity/temperature properties
- excellent ageing resistance
- compatible with all sealing materials

Specifications and Approvals:


API GL 5
MAN 342 Typ M1
MB-Approval 235.0
MIL-L 2105 D
ZF-TE-ML 05A, 16C, 17B, 19B, 21A

TECHNICAL DATA

Viscosity class	: 85W-90		
Density at 15 °C	: 0.91	g/cm ³	DIN 51757
Viscosity at 40 °C	: 201	mm ² /s	DIN 51562
Viscosity at 100 °C	: 17.6	mm ² /s	DIN 51562
Viscosity index	: 91		DIN ISO 2909
Flash point	: 206	°C	DIN ISO 2592
Pour point	: -22	°C	DIN ISO 3016
ASTM colour	: 6		DIN 51578

APPLICATION

For high-load motor vehicle transmissions, particularly axle drives with hypoid gearing.



PRODUKTINFORMATION



INSTRUCTIONS

During selection, keep to the viscosity class stipulated by the transmission manufacturer. Miscible with all branded gear oils. Fully effective only when used alone. Only use in manual transmissions for which API GL 5 oils have been stipulated.

AVAILABLE PACK SIZE

Hypoid Gear Oil SAE 85W-90	500 ml	Part no. 1404 D-GB-I-E-P
	1 l	Part no. 1035 D-GB-I-E-P
	1 l	Part no. 1956 D-RUS-UA
	1 l	Part no. 8968 D-NL-F-GR-ARAB
	20 l	Part no. 1047 D
	60 l	Part no. 1031 D
	205 l	Part no. 2165 D
	bulk oil	Part no. 1032

PI 09/09/08

Our information is based on thorough research and may be considered reliable, although not legally binding.

