

Gear Protect

DESCRIPTION

Gear Protect is a fully synthetic and oil-soluble gear oil additive which has been newly developed according to the latest technology for use in modern manual, auxiliary and differential transmissions. The surface-active components of high-pressure and wear-protection additives reduce wear and guarantee optimum transmission operation.

PROPERTIES

- reduces wear
- improves gear change performance
- increases smoothness and limp-home properties
- reduces transmission noise
- stable under continuous high loads
- secures optimum transmission operation

TECHNICAL DATA

| | |
|--------------------|-----------------------------------|
| Basis | : synthetic additives/carrier oil |
| Colour | : green |
| Density at 15 °C | : 0.94 g/cm ³ |
| Flash point | : > 180 °C |
| Pour point | : -25 °C |
| Viscosity at 40 °C | : 80 mm ² /s |

APPLICATION

For vehicle manual, auxiliary and differential transmissions. Not to be used in motorbikes or fully automatic transmissions and differential transmissions with self locking differential.

INSTRUCTIONS

One 80 ml tube is sufficient for 2 litres of gear oil. Before adding, the corresponding amount of gear oil must be removed from the transmission using the tube provided and disposed of in accordance with the regulations. Single addition at any time, particularly during oil changes and repairs.

AVAILABLE PACK SIZE

| | | |
|--------------|-------|---------------|
| Gear Protect | 80 ml | Part no. 1007 |
|--------------|-------|---------------|

PI 01/02/01

Our information is based on thorough research and may be considered reliable, although not legally binding.

