

## Glanz-Zink-Spray (Bright Zinc Spray)

### DESCRIPTION

Bright Zinc Spray is an active means of cathodic corrosion protection. The resistant, flexible, heat-resistant zinc film which is produced protects iron and steel components from rust and corrosion. Bright Zinc Spray can also be used as the only means of corrosion protection.

### PROPERTIES

- excellent corrosion protection
- smooth, pore-free film
- high zinc content
- electrically conductive
- quick drying and can be painted over
- high heat resistance
- spot weldable

### TECHNICAL DATA

Colour	: grey, bright
Zinc purity	: > 99 %
Proportion of zinc	: > 99 % (as a dry film)
Binder	: special resins
Temperature range	: up to 250 °C
Density	: 1.95 g/cm <sup>3</sup>
Drying time	: 5-7 min. dust dry 20-30 min. touch dry can be painted over after 8 hours
Propellant	: propane/butane

### APPLICATION

Used to protect iron and steel components from rust and corrosion. Suitable for repairing all damaged forms of galvanising (hot-dip, flame spraying and electroplated zinc). Bright Zinc Spray can also be used as the only means of weather-resistant corrosion protection.

### INSTRUCTIONS

Shake can vigorously for at least 1 minute before use. Spray onto clean, dry, degreased metallic surfaces. Can be painted over after 8 hours.  
Layer thickness of the zinc film dry after a single spraying: 25-35 µm.

**After use, clear spray nozzle by inverting can and spraying until only the propellant emerges.**

### AVAILABLE PACK SIZE

Bright Zinc Spray                      400 ml Aerosol,                      Part no. 1640

PI 03/06/08

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

