

Hart-Wachs (Hard Wax)

DESCRIPTION Hard Wax protects new, finished paintwork from aggressive environments and frequent car washing. Hard Wax is easy to use and reliably protects paint surfaces from harmful effects over long periods while preserving their original sheen.

PROPERTIES

- radiant high gloss
- optimum protection against aggressive environments
- super-easy to polish
- economical to use
- good long-term protection

TECHNICAL DATA

Basis	: waxes/silicones
Colour	: light green
Density	: 0.99 g/cm ³
Flash point	: > 61 °C
pH-value	: n.a.
Solubility	: insoluble in water
Viscosity	: viscous

APPLICATION Specially prepared for coloured and metallic paints, as new or correspondingly prepared. Optimum sealing against the weather for paint surfaces.

INSTRUCTIONS First, thoroughly clean the surfaces to be polished and dry them carefully. Shake Hard Wax vigorously before use and pour onto a soft rag, polishing cloth or sponge. Apply thinly and evenly to the paint surface using circular movements. Only treat one section at a time. Allow Hard Wax to dry until it forms a matt coat. Polish the area using a clean, dry cloth. Do not use under direct heat or on warm paint surfaces. Regular application gives the optimum care.

AVAILABLE PACK SIZE

Hard Wax	600 ml	Part no. 1530
----------	--------	---------------

PI 01/02/01

Our information is based on thorough research and may be considered reliable, although not legally binding.

