

Hydraulic tappet additive

DESCRIPTION High performance additive that damps down noise generation of contaminated and sticky hydraulic tappets. Cleans valve bores and thus ensures optimal functioning again.

PROPERTIES

- improves the lubrication properties of the oil
- cleans valve bores
- suitable for use in vehicles with turbochargers and vehicles with catalytic converters
- prevents engine noises caused by hydraulic tappets

TECHNICAL DATA

| | | |
|---------------------|---------------------------|-----------|
| Color | : yellowish | |
| Appearance | : viscous liquid | |
| Density at +20 °C | : 0.895 g/cm ³ | DIN 51757 |
| Viscosity at +40 °C | : 510 mm ² /s | DIN 51562 |

AREAS OF APPLICATION For all gasoline and diesel engines. Can be mixed with all commercially available motor oils

APPLICATION One 300 ml can of Liqui Moly hydraulic tappet additive is sufficient for up to 6 liters motor oil. The product can be added at any time. After adding, run the engine until warm. For a lasting effect, Liqui Moly Hydraulic tappet additive must be added after each oil change.

Note:
Not suitable for use on motorbikes with wet clutches.

AVAILABLE PACK SIZES

| | | | |
|---------------------------|--------|---------------|----------------|
| Hydraulic tappet additive | 300 ml | Part no. 1009 | D-F-NL |
| | 300 ml | Part no. 2770 | D-NL-F-GR-ARAB |
| | 300 ml | Part no. 2892 | D-GB-I-E-P |

PI 04/01/09

Our information is based on thorough research and may be considered reliable, although not legally binding.

