

Leak Finder Spray

DESCRIPTION Leak Finder Spray is a leak test fluid for compressed air, oxygen systems and CNG gas vehicles. Once the fluid is sprayed onto the surface, it indicates where the leaks are by forming bubbles over them.

PROPERTIES Water-soluble, biodegradable test fluid filled with environmentally friendly propellant. The product's high foam density guarantees economic and reliable use.

Corresponds to and fulfils the following classifications and specifications:

DVGW*-tested, DIN DVGW Reg. no: 84.01 e 557 *German Association of Gas and Water Technicians

TECHNICAL DATA

Active agent content : > 98.5 %
Foam stability : approx. 80 %
Corrosion according to DIN 30660 : no corrosion on iron, zinc, tin, copper, brass and aluminium
Compatibility with materials
PE pipe according to DIN 30657: compatible
Seals according to DIN 30660 : compatible
Lubricants according to DIN 3536 : compatible
Not compatible with all plastics. Crack formation possible with polyamide (stress-corrosion cracking).

APPLICATION

Motor vehicle maintenance
Repair work on compressed-air brake systems on HGVs, buses and commercial vehicles; welding equipment.
Industry
Test and maintenance work on compressed air and all gas lines including oxygen.
Medicine
Testing OP fittings for anaesthetic apparatus and resuscitating equipment.
Household and sport
Domestic and municipal gas lines, diving equipment and camping equipment.

INSTRUCTIONS

Spray an appropriate amount of Leak Finder Spray onto the components to be tested.

AVAILABLE PACK SIZE

Leak Finder Spray	400 ml	Part No. 3350 D-GB-I-E-P
	400 ml	Part No. 2836 D-DK-FIN-N-S

PI 02/06/09

Our information is based on thorough research and may be considered reliable, although not legally binding.

