

Leichtlauf Special AA SAE 5W-20

Spezifikationen:

API SM

ILSAC GF-4

LIQUI MOLY recommends this product for the usage in vehicles that require the following norms:

Ford WSS-M2C 930-A

Daimler Chrysler MS-6395

Honda

Mazda

Mitsubishi DiaQueen

Nissan

TECHNICAL DATA

Viscosity Class	: 5W-20		
Density at +15 °C	: 0,850	g/cm ³	DIN 51757
Viscosity at +40°C	: 47	mm ² /s	DIN 51562
Viscosity at +100°C	: 8,7	mm ² /s	DIN 51562
Viscosity index	: 166		DIN ISO 2909
Flashpoint	: 200	°C	DIN ISO 2592
Pourpoint	: -35	°C	DIN ISO 3016
TBN	: 7,4	mg KOH/g	DIN ISO 3771

APPLICATION

Perfectly suited for modern japanese and american petrol engines, specially for extended oil change intervals up to 40.000KM if allowed by the engine manufacturer.

INSTRUCTIONS

The operating materials instructions of the motor vehicle and engine manufacturer must be followed. **The full performance is guaranteed only if product is used undiluted.**

AVAILABLE PACK SIZE

Leichtlauf Special AA		
SAE 5W-20	1 l	Art.Nr. 7620 D-RUS-UA
	4 l	Art.Nr. 7621 D-RUS-UA
	205 l	Art.Nr. 7622 D-RUS-UA

Our information is based on thorough research and may be considered reliable, although not legally binding.

