

Wartungs-Spray weiß (Maintenance Spray, White)

DESCRIPTION

Maintenance Spray White is an adherent, waterproof, white, high-performance lubricant. After the solvent has evaporated, the product leaves a soft film of grease.

PROPERTIES

- prevents fretting corrosion/friction corrosion
- reliable corrosion protection
- extremely adherent
- excellent lubricating action
- good water resistance
- outstanding low and high temperature properties
- clean application

TECHNICAL DATA

Colour	: white
Basis	: mineral oil (solid lubricants)
Thickener	: bentonite
Density	: approx. 1.0 g/cm ³ (after solvent has evaporated)
Drop point	
ISO 2176	: none
Consistency grade	: NLGI 2 (after solvent has evaporated)
Operating temperature range	: -30 °C to +250 °C
Propellant	: propane/butane

APPLICATION

Used for lubricating moving parts such as shafts, hinges, joints, pins, Bowden cables, slip rails, chains, springs and lock strikers etc.

INSTRUCTIONS

Shake can before use. Spray large areas without the capillary tube from about 20-25 cm. The capillary tube eases use in places which are not very accessible.


After use, clear spray nozzle by inverting can and spraying until only the propellant emerges.

AVAILABLE PACK SIZE

Maintenance Spray, White	250 ml	Part no. 3075
--------------------------	--------	---------------

PI 01/02/01


Our information is based on thorough research and may be considered reliable, although not legally binding.



PRODUKTINFORMATION



Wartungs-Spray weiß (Maintenance Spray, White)



LIQUI MOLY GMBH
Jerg-Wieland-Str. 4
D-89081 Ulm-Lehr

Postfach 28 29
D-89018 Ulm
www.liqui-moly.de

Phone: +49-(0)731/1420-13
Fax: +49-(0)731/1420-82
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230
Technische Hotline: +49-(0)731/1420-13