

Motor Oil Saver

DESCRIPTION

Motor Oil Saver reduces the oil consumption of gasoline and diesel engines. The product regenerates hardened seals made of rubber and plastic and acts against the drop in viscosity of motor oil.

PROPERTIES

- reduces oil consumption via valve stem seals and radial sealing rings
- prevents blue, smoky exhaust fumes
- prevents leaks due to leaks at elastomeric seals
- regenerates engine seals made of plastic and rubber - reduces engine noises
- prevents pollution of the environment due to oil dripping from the engine

TECHNICAL DATA

Color	: Yellow	
Appearance	: Viscous liquid	
Density at 20 °C	: approx. 0.89	g/cm ³
Viscosity at 20 °C	: 4,000	mPa.s
Flash point	: 76	°C
Pour point	: -5	°C

APPLICATIONS

For all gasoline and diesel engines. Compatible with all commercially available motor oils. Not suitable for use in motorbikes with wet clutches.

APPLICATION

One 300 ml can of Motor Oil Saver is sufficient for 4.5 liters of motor oil. The product can be added at any time. After adding, run the engine until warm. Sealing first takes effect after about 600 - 800 km. To guarantee a lasting effect, add Motor Oil Saver after each oil change.

AVAILABLE PACK SIZES

Motor Oil Saver	300 ml	Part no. 2501
-----------------	--------	---------------

PI 00/11/04

Our information is based on thorough research and may be considered reliable, although not legally binding.

