

Multi-Purpose Grease

DESCRIPTION

High-performance Multi-Purpose Grease for lubricating plain and roller bearings under normal and high loads. Suitable as a universal grease for motor vehicles and for general machine lubrication. Multi-Purpose Grease guarantees long-term lubrication, has good sealing properties, is resistant to damp and dusty environments and moves well in central lubrication systems.

PROPERTIES


- universal use
- resistant to cold and hot water
- reduces friction and wear
- high load-carrying capacity
- stable to ageing and to liquifying
- protects against corrosion
- economical to use

Complies with the certification for grease in accordance with DIN 51502 K2K-30

TECHNICAL DATA

Colour	: pale brown	
Basis	: mineral oil	
Thickener	: Li-12-hydroxystearate	
Base oil viscosity +40 °C	: 105 mm ² /s	DIN 51 562
Operating temperature range	: -30 °C to +125 °C	
Pour point	: -22 °C	
NLGI number	: 2	
Worked penetration	: 265-295	DIN 51 804
Flash point	: 230 °C	
Drop point	: 180 °C	
Ash, Oxide	: 1.2g/100 g	
Ash, Sulphate	: 1.8g/100 g	
Water resistance at 90 C	: 1	DIN 51 807
Water content	: < 0.1 g/100 g	
Neutralisation number, alkaline	: 2.0mg KOH/g	
Oil separation after 7 days and +40 °C	: 3.6g/100 g	
EMCOR test	: 0/0 (no corrosion)	DIN 51 802

.../2



PRODUKTINFORMATION



APPLICATION

Used for motor vehicles, construction and agricultural machinery and used in industry. The wide operating temperature range and the high resistance to water reduce the diversity of products required.

INSTRUCTIONS


As usual for grease. The operating instructions of the bearing and machine manufacturers must be followed.

AVAILABLE PACK SIZE

Multi-Purpose Grease	400 g	Part no. 3552
	1 kg	Part no. 3553
	1 kg	Part no. 1834
	5 kg	Part no. 3554
	25 kg	Part no. 3555
	50 kg	Part no. 3556
	180 kg	Part no. 3557

PI 02/03/07

Our information is based on thorough research and may be considered reliable, although not legally binding.



LIQUI MOLY GMBH
Jerg-Wieland-Str. 4
D-89081 Ulm-Lehr

Postfach 28 29
D-89018 Ulm
www.liqui-moly.de

Phone: +49-(0)731/1420-13
Fax: +49-(0)731/1420-82
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230
Technische Hotline: +49-(0)731/1420-13