

PTFE-Pulver-Spray (PTFE Powder Spray)

DESCRIPTION

PTFE Powder Spray is a grease-free lubricant and release agent based on PTFE (Teflon or polytetrafluorethylene). With its long-term lubricating action, this product has universal application particularly in work areas where oil or silicone-based agents cannot be used because they ruin finishing work such as painting or because of other reasons.

PROPERTIES

- easy to use
- free of oil, grease and silicones
- no taste
- high chemical resistance
- high heat resistance
- low friction
- eliminates squeaks
- suitable for care, protection and insulation

TECHNICAL DATA

Colour:	white
Basis:	PTFE
Density at 20 °C	0.58 g/cm ³
Operating temperature range:	-40 °C to +250 °C
Propellant:	propane/butane

APPLICATION

PTFE Powder Spray is a lubricant which can be used on practically any material. In automotive engineering, it is the optimum lubricant for belt mechanisms and guide rails such as those found under seats. It can also be used as a lubricant and separating agent for eliminating any type of noise from covers and seats etc. In industry it is used particularly in processing textiles and wood for bearings, slip rails, rollers, chains and threads. It also has universal application in the household. Ideally suitable as a release agent in plastics processing.

INSTRUCTIONS

Spray PTFE Powder Spray thinly and uniformly onto the clean and grease-free surface. If greater layer thickness is required, the preceding coat must be allowed to dry before applying another coat.

After use, clear spray nozzle by inverting can and spraying until only the propellant emerges.

AVAILABLE PACK SIZE

PTFE Powder Spray	400 ml	Aerosol	Art.Nr. 3076 D-GB-I-E-P
	400 ml	Aerosol	Art.Nr. 2871 D-DK-FIN-N-S

PI 03/11/08

Our information is based on thorough research and may be considered reliable, although not legally binding.