PRODUKTINFORMATION

Lack-Glanz-Creme
(Paint Polishing Cream)

DESCRIPTION

Paint Polishing Cream has been specially developed to restore the original appearance to coloured and metallic paints which have become matt and unsightly due to the effects of radiation from the sun or aggressive industrial atmospheres. Because of its creamy consistency, Paint Polishing Cream can be applied sparingly while preserving the paintwork and enhancing its sheen.

PROPERTIES

- radiant gloss
- easy to use
- good long-term protection
- optimum protection against aggressive environments
- evens out light scratches

TECHNICAL DATA

Basis	: waxes, polishing pigments	
Form	: paste-like	
Colour	: yellow	
Odour	: characteristic	
Density at 20 °C	: 0.96	g/cm³
pH-value	: 7.8	
Solubility in water	: emulsifiable	
Flash point	: 70	°C
Viscosity at 40 °C	: > 7	mm²/s

APPLICATION

Specially developed for coloured and metallic paints from new to slightly matt. The original appearance is easily restored to mildly weathered and matt paintwork.

INSTRUCTIONS

First, thoroughly clean the paint surfaces to be treated and dry them carefully. Remove Paint Polishing Cream from the can using a soft rag, polishing cloth or sponge and apply thinly and evenly using light pressure and circular movements. Only treat one section at a time. Allow Paint Polishing Creme to dry until it forms a matt coat. After this, remove with a clean, dry cloth or polishing fibres and polish the surface to a high sheen. Do not use under direct heat or on warm paint surfaces. Regular application gives the optimum results.

AVAILABLE PACK SIZE

Paint Polishing Cream	300 g	Part no. 1532

PI 01/02/01

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GMBH
Jerg-Wieland-Str. 4
D-89081 Ulm-Lehr

Postfach 28 29
D-89018 Ulm
www.liqui-moly.de

Phone: +49-(0)731/1420-13
Fax +49-(0)731/1420-82
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230
Technische Hotline: +49-(0)731/1420-13