

## Racing 4T SAE 20W-50

### DESCRIPTION

Racing 4T SAE 20W-50 is a high-performance engine oil which is formulated according to the latest technology. Selected base oils and a high additive content guarantee optimum lubrication under extreme running conditions.

### PROPERTIES

- universal application
- high lubricant-film stability and excellent wear protection
- high shear and ageing stability
- outstanding cleaning and dispersion properties
- prevents black sludge
- low evaporation loss and oil consumption
- miscible with all commercially available engine oils
- tested for compatibility with catalytic converters

### classifications and specifications:

API SG

### TECHNICAL DATA

Viscosity class	: 20W-50
Density at 15 °C	: 0.89 g/cm <sup>3</sup>
Viscosity at 40 °C	: 150 mm <sup>2</sup> /s
Viscosity at 100 °C	: 17.5 mm <sup>2</sup> /s
Viscosity index	: 128
Flash point	: 240 °C
Pour point	: -28 °C
ASTM colour	: 3.5

### APPLICATION

Four-stroke motorbike engines.

### INSTRUCTIONS

The operating instructions of the engine manufacturer must be followed.

### AVAILABLE PACK SIZE

Racing 4T 20W-50	1 l	Part no. 1500 D-GB-I-E-P
	1 l	Part no. 1755 Japan
	1 l	Part no. 2762 D-NL-F-GR-

### ARAB

5 l	Part no. 1501 D-GB-I-E-P
20 l	Part no. 1560
60 l	Part no. 1561

PI 05/01/09

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

