

## Racing Chain Lube

### DESCRIPTION

High-quality thermostable, extremely adherent, throw-proof synthetic lubricant compound. After the solvent has evaporated, the product leaves an extremely adherent, soft film of grease. Also suitable for O-ring chains.

### PROPERTIES

- extremely good adherence
- throw-proof
- outstanding corrosion protection
- high load-carrying capacity
- cold, hot and splash water resistant
- excellent penetration action
- outstanding friction and wear reduction
- reduces chain elongation on high-performance motorbikes
- high performance only when used alone.

### TECHNICAL DATA

Basis	:	Synthetic oil/additives
Colour	:	yellowish
Operating temperature range	:	-30 °C to +180 °C short term 200 °C
Water resistance at 90 °C DIN 51,807	:	0
Biodegradability CEC-L-33-A-93	:	80 %

### APPLICATION

Initial and maintenance lubrication of power-transmission chains. Especially suitable for dusty, dirty and corrosive environments. Due to extremely good adherence, especially suitable for high-load, fast-running chains

### INSTRUCTIONS

Carefully clean chain with solvent such as rapid cleaners. Apply by spraying. The lubricant attains its final consistency and adherence once the solvent has rapidly evaporated.

### AVAILABLE PACK SIZE

Racing Chain Lube                      250                      ml                      Part no. 1508 D-GB-I-E-P

PI 03/01/09

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

