

## Racing HD Classic SAE 50

### DESCRIPTION

Racing HD Classic SAE 50 is a high-performance engine oil which is formulated according to the latest technology. Selected base oils and a high additive content guarantee optimum lubrication under extreme running conditions.

### PROPERTIES

- results in quiet running engine
- high lubricating film stability and optimum wear protection
- low evaporation loss and oil consumption
- high stability to ageing and absolute shear stability
- excellent cleaning and dispersion properties
- prevents black sludge
- miscible with all commercially available engine oils
- tested for compatibility with catalytic converters

Corresponds to and fulfils the following classifications and specifications:

API SG  
CCMC, G4  
**Performance Level**  
MIL-L-46152 D

### TECHNICAL DATA

Viscosity class	: 50	
ASTM colour	: 5	
Density at 15 °C	: 0.90	g/cm <sup>3</sup>
Viscosity at 40 °C	: 240	mm <sup>2</sup> /s
Viscosity at 100 °C	: 20	mm <sup>2</sup> /s
Evaporation loss (Noack)	: 3	%
Flash point	: 270	°C
Pour point	: -16	°C

### APPLICATION

Four-stroke motorbike engines - especially Harley-Davidson.

### INSTRUCTIONS

The operating instructions of the engine manufacturer must be followed.

### AVAILABLE PACK SIZE

Racing HD Classic SAE 50	1 l	Part no. 1572
	5 l	Part no. 1573
	20 l	Part no. 1574
	60 l	Part no. 1575
	205 l	Part no. 1576

PI 01/02/01

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

