

Racing Synth 4T SAE 10W-60

DESCRIPTION

Racing Synth 4T SAE 10W-60 is a fully synthetic, high-performance engine oil developed for use in four-stroke high-performance engines for two-wheel road and racing machines. The synthetic base oils and high-quality additives satisfy and exceed the requirements of the most state-of-the-art motorbike engine designs.

PROPERTIES

- optimum lubrication under extreme conditions
- high lubricant and ageing stability
- low oil consumption and evaporation loss
- very good wear protection
- tried and tested with exhaust catalytic converters
- suitable for wet clutches
- outstanding engine cleanliness
- miscible and compatible with commercially available engine oils.
- tested on racing machines


Corresponds to and fulfils the following classifications and specifications:

API SG/SH

TECHNICAL DATA

Basis	:	synthetic oil/additives
Viscosity class	:	10W-60
ASTM colour number	:	3.5
Density at 15 °C	:	0.86 g/cm ³
Viscosity at 40 °C	:	163.0 mm ² /s
Viscosity at 100 °C	:	24.0 mm ² /s
Viscosity index	:	179
Flash point	:	238 °C
Pour point	:	-35 °C
Evaporation loss	:	6.9 %
Ash, Sulphate	:	1.5 g/100 g
Strong base number	:	12.0 mg KOH/g

.../2



PRODUKTINFORMATION



APPLICATION Optimum for high-stress four-stroke road and racing machines.

INSTRUCTIONS The operating instructions of the motorcycle and engine manufacturers must be followed.

AVAILABLE PACK SIZE	Racing Synth 4T SAE 10W-60	1 l	Part no. 1525
		5 l	Part no. 1526
		20 l	Part no. 1527

PI 02/06/04

Our information is based on thorough research and may be considered reliable, although not legally binding.

