

## Radiator Sealant

### DESCRIPTION

Radiator Sealant is a dispersion for sealing leaks in water-cooling systems in motor vehicles. The product reliably seals hair cracks and small leaks. The solids dispersion is stabilised in carrier fluid.

### PROPERTIES

- permanently and reliably seals hairs and small leaks
- compatible with all commonly used cooling water modifiers and antifreezes
- no negative side effects on the water pump or heating circuit
- suitable for aluminium radiators

### TECHNICAL DATA

Form	: liquid
Colour	: light white with polyglitter
Density at 20 °C	: 1.07 g/cm <sup>3</sup>
Viscosity	: at least 30 sec. (Ford cup 4 mm nozzle)
Solubility in water	: miscible

### APPLICATION

Used for sealing small leaks in cooling circuits of passenger motor vehicles, commercial vehicles, buses and two-wheel vehicles. Also suitable for cooling circuit with filters.

### INSTRUCTIONS

Shake container before use. Run the heating system. With the engine running, pour the contents into the cooling fluid at operating temperature and allow the engine to continue running for a further 10 minutes. The contents is sufficient for 10 litres of coolant.

### AVAILABLE PACK SIZE

Radiator Sealant	150 ml	Part no. 3330
------------------	--------	---------------

PI 02/09/05

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

