

Super Low-Friction SAE 10W-40

DESCRIPTION

High-tech synthetic all-season, low-friction motor oil. Super Low-Friction was developed for the toughest requirements of modern, high-performance gasoline and diesel engines without extended maintenance intervals. Tested for use with catalytic converters and turbochargers. Saves fuel and provides optimal wear protection. The formulation has a beneficial effect on sealing materials and thus on the leaktightness of engines. That makes Super Low-Friction Motor Oil especially suitable for vehicles with mileages over 60,000.

PROPERTIES

- Smooth engine running
- Especially suitable for vehicles with mileages over 60,000
- Beneficial effect on sealing materials and thus on the leaktightness of engines
- Rapid oil delivery at low temperatures
- High lubrication reliability at high and low temperatures
- High shear and ageing stability
- Very good wear protection
- Saves gasoline and reduces pollutant emission
- Optimum engine cleanliness
- Mixable and compatible with commercially available motor oils
- Tested with catalytic converters and performance proven with turbochargers

Specifications and approvals:


API	SL/CF
ACEA	A3-04/B4-04
VW	501 01 and 505 00 (Issue 2005)
MB-Approval	229.1

LIQUI MOLY also recommends this product for vehicles for which the following specifications are required:

VW	500 00
Peugeot/Citroen (PSA)	B71 2294

TECHNICAL DATA

Viscosity class	:	10W-40	
Density at +15 °C	:	0.880	g/cm ³ DIN 51757
Viscosity at +40 °C	:	91.1	mm ² /s DIN 51562
Viscosity at +100 °C	:	13.7	mm ² /s DIN 51562
Viscosity index	:	152	DIN ISO 2909
Flash point	:	228	°C DIN ISO 2592
Pour point	:	- 33	°C DIN ISO 3016
ASTM color number	:	2.5	DIN 51578
Ash, sulphate	:	1.18	g/100 g DIN 51575



.../2

PRODUKTINFORMATION



AREAS OF APPLICATION

Especially suitable for vehicles with mileages of over 60,000 as well as for use in modern gasoline, passenger vehicle diesel and turbocharged engines.

APPLICATION

The operating instructions of the vehicle and engine manufacturers must be followed.

AVAILABLE PACK SIZES

Super Low-Friction SAE 10W-40	1 l	Part no. 1300 D-GB-I-E-P
	1 l	Part no. 1928 D-RUS-UA
	1 l	Part no. 2454 D-NL-F- GR-ARAB
	1 l	Part no. 2624 D-PL-H-RO-TR
	1 l	Part no. 2742 GB-AUS
	1 l	Part no. 9503 D-GB-F-ARAB
	4 l	Part no. 1916 D-RUS-UA
	4 l	Part no. 2196 D-GB-I-E-P
	4 l	Part no. 2455 D-NL-F- GR-ARAB
	4 l	Part no. 2625 D-PL-H-RO-TR
	4 l	Part no. 9504 D-GB-F-ARAB
	5 l	Part no. 1301 D-GB-I-E-P
	5 l	Part no. 1858 D-NL-F-GR-ARAB
	5 l	Part no. 1929 D-RUS-UA
	5 l	Part no. 2743 GB-AUS
	5 l	Part no. 9505 D-GB-F-ARAB
	20 l	Part no. 1304
	60 l	Part no. 1302
	60 l	Cont. Part no. 1325
	120 l	Cont. Part no. 1326
	205 l	Part no. 1303
	1000 l	Part no. 1330
	1000 l	Cont. Part no. 4292 Export

PI 16/04/10

Our information is based on thorough research and may be considered reliable, although not legally binding.

