

THT Special Diesel Oil SAE 15W-40

DESCRIPTION

Touring High Tech Special Diesel Oil SAE 15W-40 is an all-year-round, modern, high-performance engine oil specially formulated for aspirated and turbocharged diesel engines with and without charge air cooler. A high additive content guarantees optimum lubrication under all running conditions.

PROPERTIES

- Universal use for petrol and diesel engines with and without exhaust-gas turbocharging and with and without charge air cooling.
- outstanding cold-start behaviour
- stable to ageing and viscosity stable
- high lubricating film stability and reliable wear protection
- optimum engine cleanliness and very good dispersant properties
- miscible with all commercially available engine oils

Specifications / Approvals:


API CF/CG-4
ACEA B4-04/E2-96 Issue 5
MB-approval 228.3, 229.1
MAN 271
Allison C-4
Caterpillar TO-2
Mack EO-L
MIL-L-2104 E
Volvo VDS

LIQUI MOLY recommends this product for vehicles for which the following specifications are required

VW 501 01 (old) und 505 00
MTU Typ 2

TECHNICAL DATA

Viscosity class	: 15W-40
Density at 15 °C	: 0.885 g/cm ³
Viscosity at 40 °C	: 108 mm ² /s
at 100 °C	: 14.0 mm ² /s
Viscosity index	: 137
Flash point	: +225 °C
Pour point	: -30 °C
Strong base number TBN	: 10.9 mg KOH/g
ASTM colour	: 3



.../2

PRODUKTINFORMATION



APPLICATION For aspirated and turbocharged diesel engines with and without exhaust-gas turbocharging and with and without charge air cooling.

INSTRUCTIONS The operating instructions of the motor vehicle and engine manufacturer must be followed.

**AVAILABLE
PACK SIZE**

THT Special Diesel Oil
SAE 15W-40

1 l	Part no.1070 D-GB-I-E-P
5 l	Part no.1073 D-GB-I-E-P
20 l	Part no.1071
60 l	Part no.1072
205 l	Part no.1075
5 l	Part no.1864 D-NL-F-GR-ARAB
1 l	Part no.2190 D-PL-H-RO-TR
5 l	Part no.2191 D-PL-H-RO-TR

PI 13/04/10

Our information is based on thorough research and may be considered reliable, although not legally binding.

