PRODUKTINFORMATION

Wax Coating

DESCRIPTION

Extremely adherent, wax-based corrosion protection containing state-of-the-art agents. The adherent, permanently elastic and transparent protective film offers outstanding, reliable, long-term protection for inside and outside storage. Resistant to salt water and corrosive influences. The thin coating does not impair any subsequent welding work.

PROPERTIES

- Transparent, adherent and waterproof protective film
- Excellent long-term protection
- Good resistance to salt water
- Optimum corrosion protection
- Can be used for inside and outside storage

TECHNICAL DATA

Base	: wax/solvents		
Appearance	: light brown/clear		
Propellant	: propane/butane		
Density at +20 °C	: 0.69	g/cm³	DIN 51757
Film thickness	: 15 - 50	µm	

AREAS OF APPLICATION

For inside and outside storage, transport and dispatch of machines and metal components. The thin coating does not impair any subsequent welding work. Normal handling is possible soon after the non-oil-based film has been applied.

APPLICATION

Shake can well before use and apply by spraying. The coating thickness is between 15 µm and 50 µm depending on environmental conditions. Apply to clean, dry surfaces. Apply several coats to increase protection against corrosion. The contents of the can should be at room temperature during application. When spraying in enclosed spaces, make sure that there is sufficient ventilation. **After use, clear spray nozzle by inverting can and spraying until only the propellant emerges.**

Note: Engine compartment cleaner, part number 3326, can be used for removal of the wax coating. The application notes can be found in the product information for part no. 3326.

AVAILABLE PACK SIZES

Wax Coating	300 ml	Part no. 3311	D-GB-E-F-NL

PI 04/07/07

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GMBH
Jerg-Wieland-Str. 4
D-89081 Ulm-Lehr

Postfach 28 29
D-89018 Ulm
www.liqui-moly.de

Phone: +49-(0)731/1420-13
Fax +49-(0)731/1420-82
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230
Technische Hotline: +49-(0)731/1420-13