

White Universal Grease

DESCRIPTION

White Universal Grease has been developed for use on high-load plain, roller and rocker bearings. The solid lubricants contained in the product guarantee high load-carrying capacity for clean lubrication points and longlife lubrication. Suitable for use on equipment in contact with food.

PROPERTIES


- safety lubricant for lubrication points free of contaminants
- longlife lubrication
- economical because of extended lubrication intervals
- cost reduction on maintenance and lubricant due to minimisation of breakdown and maintenance times
- suitable for use in food technology
- harmless to health, non-poisonous and satisfies the requirements of the regional institute of trading (Germany)
- good high-pressure properties

Complies with the certification for grease in accordance with DIN 51502 KF2K-30

TECHNICAL DATA

Colour and consistency	: white, smooth and soft	
Basis	: mineral oil with a mixture of white solid lubricants	
Thickener	: lithium soap	
Base oil viscosity at 40 °C	: 108 mm ² /s	DIN 51562
NLGI number	: 2	DIN 51818
Worked penetration	: 275-295	DIN 51804
Drop point	: +195 °C	DIN ISO 2176
Operating temperature range	: -30 °C to +120 °C Short periods up to +130 °C	
Four-ball test	: 3800 N welding load 3600 N material load	DIN 51350.4
Water resistance at 90 °C	: 0	DIN 51807
EMCOR test	: 0 (no corrosion)	

.../2



PRODUKTTINFORMATION




APPLICATION Suitable for lubricating high-load plain, roller and rocker bearings, spindles and guides on machines in the food, drinks, paper, textile and clothing industries as well as on domestic appliances.

INSTRUCTIONS As usual for grease. Do not mix with other greases.

**AVAILABLE
PACK SIZE** White Universal Grease 400 g cartridge Part no. 8918

PI 04/01/07

Our information is based on thorough research and may be considered reliable, although not legally binding.



LIQUI MOLY GMBH
Jerg-Wieland-Str. 4
D-89081 Ulm-Lehr

Postfach 28 29
D-89018 Ulm
www.liqui-moly.de

Phone: +49-(0)731/1420-13
Fax: +49-(0)731/1420-82
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230
Technische Hotline: +49-(0)731/1420-13